



# JUMPSUIT CUTTING INSTRUCTIONS

©2009 by the owner of the rights in the work. www.jumpsuit.it

## SUPPLIES NEEDED

- 3 YARDS OF 54" WIDE FABRIC
  - SHARP SCISSORS
  - REMOVABLE MARKING MEDIUM (chalk, wax, tailor's tack, etc.)
  - 1/4" NONSLIP/SLIP ZIPPER
  - THREAD
  - SEWING MACHINE
- optional:
- 1/2 YARD OF THINNER POCKET FABRIC
  - FUSIBLE INTERFACING

## CUTTING INSTRUCTIONS

- Print pattern. You can print this document (that on sheets of standard size paper and tape the pieces together, or print on a wide-format printer 36" or wider). Print always at the same size for approximately 85%. If available to you, the BFD recommends wide-format printing.
- Check your pattern is printed out along the convenient markings to remove any excess paper. This template should fit exactly on a 54" wide or larger piece of fabric that has been folded in half. If your fabric is less than 54" wide, see NOTE A. For maximum yield this pattern is laid out for fabric that does not have a direction. For fabric with a nap, such as velvet or corduroy or fabric with a clear directional print see NOTE B.
- Fold your fabric in half along the appropriate grain matching selvage edge to selvage edge. Schedule to the self-finished edge of fabric. This narrow border keeps the fabric from unraveling or fraying. Often it has an edge that resembles any fringe, though just as frequently, it's a clearly finished line with a finish. Iron this edge in your cut pieces as the texture frequently differs from the main body of the fabric.
- Trace the paper template on top your fabric, matching the folded edge of the fabric with the side of the paper marked "folded edge".
- Place pins throughout the template pinning together both layers of fabric as well as the paper.
- Cut around the perimeter of each piece.
- Leaving the pins in place, you will next need to snip each of the notches, taking care to not snip beyond the end of the "clip".
- Transfer to the U-shaped markings that are found throughout the pattern. Some indicate notches and others indicate, which others indicate you are at a pattern piece will arise.
- Mark all interior darts, waist, or other removable, nonpermanent notches. A tailor's tack may also be used. These narrow darts, waist, or notches are marked in the following order:  
They will be found on the Pant Back, Back Back, and your pattern contains four darts that you will find a mark on the Bodice Front.
- OPTIONAL: Cut fusible interfacing pieces (see NOTE C for more info). Pattern pieces that are fusible will be marked with the direction "Cut 2 Fusible" or "Cut 1 Fusible". These pieces are: the Collar, Fly, Fly Facing, Front Pocket Facing, and Front Pocket Backing. To cut the fusible, lay the material down with the glue side facing up, then place your pattern down and cut around the perimeter of each piece and notch.
- For the Front Pocket Bag cut of a lighter pecking material. If you are not using a pecking material, then the Front Pocket Bag may be cut alongside your other pattern pieces. *Pecking is used to make both in case of thicker material - to not fold or to keep on top of the pattern.*

**NOTE A: FABRIC LESS THAN 54" WIDE**  
If your fabric is less than 54" wide, you will need to use each pattern piece individually. This paper template includes a layout for your fabric taking care to position the pattern pieces on the fabric in a rational way. The quantity instructions and quantities are all marked on each pattern piece for ease of use. To mark the quantities, mark for the single line with two arrows at each end. When this pattern is used on fabric that is less than 54" wide, the quantity of each piece will be marked on the pattern. When marking fabric on the fabric, these two lines should be used to indicate the width of your fabric. The quantity of each piece will be marked on the pattern. When the top and bottom arrows are equivalent from the side of your fabric then the quantity is a correct quantity.

**NOTE B: FABRIC WITH NAP OR DIRECTIONAL PATTERN**  
For fabric with a nap or directional fabric, such as velvet, corduroy, or fabric with a directional print, or for marking stripes such as plaid, you will need to use the pattern pieces individually then lay them on your fabric, covering the top and bottom arrows from each side of the pattern in the same position.

**NOTE C: USING FUSIBLE INTERFACING**  
Fusible interfacing is a material that is used to reinforce, stabilize, and reduce crease lines in a garment. While the use of fusible interfacing is optional, the BFD recommends using fusible interfacing on the waistband of all jumpsuits.

Size Auto  
Front Pocket  
Cut 2 Pocketing\*  
\*or cut 2 self

Before cutting your fabric measure this square to make sure that the pattern is scaled correctly\*  
\*Some printers and software will automatically scale large scale images which will affect the fit.  
The inner square should measure 4" x 4"  
The outer square should measure 12cm x 12cm

Size Auto  
Front Pocket  
Back  
Cut 2 Self  
Cut 2 Fusible

Size Auto  
Pant Back  
Cut 2 Self

Size Auto  
Fly  
Cut 1 Self  
Cut 1 Fusible

Size Auto  
Collar  
Cut 2 Self  
Cut 2 Fusible

Size Auto  
Pant Front  
Cut 2 Self

Size Auto  
Front Pocket  
Facing  
Cut 2 Self  
Cut 2 Fusible

Size Auto  
Sleeve Front  
Cut 2 Self

Size Auto  
Sleeve Back  
Cut 2 Self

Belt Loops  
Cut 1 Self

Size Auto  
Fly Facing  
Cut 1 Self  
Cut 1 Fusible

Size Auto  
Bodice Back  
Cut 1 on Fold

Size Auto  
Bodice Front  
Cut 2 Self

Size Auto  
Back Pocket  
Cut 2 Self

Size Auto  
Back Waistband  
Cut 1 Self - On Fold

Size Auto  
Front Waistband  
Cut 2 Self