

- SUPPLIES NEEDED**
- 1/2 YARDS OF 54" WIDE FABRIC
 - SHARP SCISSORS
 - REMOVABLE MARKING MEDIUM (chalk, wax, tailor's tack, etc.)
 - 1 - 24" NON-SEPARATING ZIPPER
 - THREAD
 - SEWING MACHINE (optional)
 - 1/2 YARD OF THINNER POKER FABRIC
 - FUSIBLE INTERFACING

- CUTTING INSTRUCTIONS**
1. Print pattern. You can print this document and on sheets of standard size paper and tape the pieces together, or print on a wide-format printer (36" or wider). Print sheets after the version (or approximately) 5:12. If available to you, the REE's recommendations will format printing.
 2. Once your pattern is printed, cut along the recommender's rectangle to remove any excess paper. This template should fit roughly on a 36" wide or larger piece of fabric that has been folded in half. If your fabric is less than 54" wide, see **NOTE A**. For maximum fold this pattern is laid out for fabric that does not have a direction. For fabric with a nap, such as velvet or corduroy or fabric with a clear directional print, see **NOTE B**.
 3. Fold your fabric in half along the lengthwise grain matching selvage edge to selvage edge. Schedule in the self finished edge of fabric. This narrow border keeps the fabric from stretching or fraying. Often it has an edge that resembles iron fringe; if that iron is frayed, a clearly finished line will be found. Avoid this edge in your cut pieces as this section frequently differs from the main body of the fabric.
 4. Place the paper template on top of your fabric, matching the folded edge of the fabric with the side of the paper marked "folded edge".
 5. Place pins throughout the template pinning together both layers of fabric as well as the paper.
 6. Cut around the perimeter of each piece.
 7. Leaving the piece of fabric, you will need to strip each of the notches, taking care to not strip beyond the end of the "I" shape?
 - Notches are all "I" shaped markings that are found throughout the pattern.
 - Some notches indicate seam allowances, while others will help you line up pattern pieces while sewing.
 - This marker will help you line up pieces, being together both layers of fabric and the pattern, mark the corner of each notch to avoid any of the four corners of the pattern.
 - A notches mark may also be used.
 8. **OPTIONAL:** Cut fusible interfacing pieces. **NOTE C:** For more info. Pattern pieces that use fusible will be marked with the direction "Cut 2 Fusible" or "Cut 1 Fusible". These pieces are: the Collar, Fly, Fly Facing, Front Pocket Facing, and Front Pocket Backing. To cut the fusible, lay the material down with the grain side facing up, then place your pattern down and cut around the perimeter of each piece and notch.
 9. Cut the Front Pocket Backing and the Front Pocket Facing. If you are not using a pocketing material, then the Front Pocket Bag may be cut alongside your other pattern pieces. *Pocketing is used to make both in cases of thicker material - 1" or thicker or weight of padding or any part of the case.*

NOTE A: FABRIC LESS THAN 54" WIDE
If your fabric is less than 54" wide, you will need to cut out pattern pieces individually from the paper template and piece them together on your fabric. This process requires extra care and attention as all notches or notches must be cut on the same side of the fabric. For fabric with a nap, such as velvet or corduroy or fabric with a clear directional print, see **NOTE B**.

NOTE B: FABRIC WITH NAP OR DIRECTIONAL PATTERN
For fabric with a nap, such as velvet or corduroy, fabric with a clear directional print, or fabric with a directional pattern, such as plaid, you will need to cut the pattern pieces individually from the paper template. For fabric with a nap, you will need to cut the pattern pieces individually from the paper template. For fabric with a directional pattern, you will need to cut the pattern pieces individually from the paper template.

NOTE C: USING FUSIBLE INTERFACING
Fusible interfacing is a non-woven fabric that is used to stabilize, strengthen, and add structure to pattern pieces. When the use of fusible interfacing is required, the pattern pieces will be marked with the direction "Cut 2 Fusible" or "Cut 1 Fusible".

