

- SUPPLIES NEEDED**
- 3 YARDS OF 54" WIDE FABRIC
 - SHARP SCISSORS
 - REMOVABLE MARKING MEDIUM (chalk, wax, tailor's tack, etc.)
 - 1 - 24" NON-SEPARATING ZIPPER
 - THREAD
 - SEWING MACHINE
- OPTIONAL:**
- 1/2 YARD OF THINNER POCKET FABRIC
 - FUSIBLE INTERFACING

- CUTTING INSTRUCTIONS**
1. Print pattern. You can print this document third on sheets of standard size paper and tape the pieces together, or print on a wide-format printer (36" or wider). Print shops offer this service for approximately \$12. If available to you, the 85% recommended wide-format printing.
 2. Once your pattern is printed, cut along the outermost rectangle to remove any excess paper. This template should fit exactly on a 14" wide or larger piece of fabric that has been folded in half. If your fabric is less than 54" wide, simply mark a vertical crease on fabric with a clear directional pin on **NOTE 1**.
 3. Fold your fabric in half along the lengthwise grain matching selvedge edge to selvedge edge. Schage in the self finished edge of fabric. The narrow binder keeps the fabric from wrinkling or fraying. Often it has an edge that resembles fine fraying, though you as frequently, clearly, finished line will be found. Avoid the edge or your cut pieces as the pattern frequently differs from the main body of the fabric.
 4. Place the paper template on top your fabric, matching the folded side of the fabric with the side of the paper marked "folded edge".
 5. Place pins throughout the template pinning together both layers of fabric as well as the paper.
 6. Cut around the perimeter of each piece.
 7. Leaving the pins in place, you will need to snip each of the corners, taking care to not snip beyond the end of the U shape!
 - **Notches are 1/4" deep markings that are found throughout the pattern.**
 - **Some notches indicate seam allowances widths, while others will help you align your pattern piece while sewing.**
 8. Mark all interior darts/bags. Using a pin, bring together both layers of fabric and the pattern, mark the center of each dart/bag with chalk, wax or other removable, suspension mark. A tailor's tack may also be used. This will be done on the final piece. **Understand, mark all of your pattern pieces are done this way you will find a mark on the fabric piece.**
 9. **OPTIONAL:** Cut fusible interfacing pieces (see **NOTE C** for more info). Pattern pieces that use fusible will be marked with the direction "Cut 2 Fusible" or "Cut 1 Fusible". These pieces are: the Collar, Fly, Fly Facing, Front Pocket Facing, and Front Pocket Backing. To cut the fusible, lay the material down with the glue side facing up, then place your pattern down and cut around the perimeter of each piece and snip.
 10. Cut the Front Pocket Bag out of a lighter pocketing material. If you are not using a pocketing material, then the Front Pocket Bag may be cut alongside your other pattern pieces. Pocketing is used to make bags or cases of lighter material - You will find an example of pocketing on any pair of fabric jeans.

NOTE A: FABRIC LESS THAN 54" WIDE
If your fabric is less than 54" wide you will need to cut each pattern piece individually from the paper template and create a narrow binder to keep your fabric from wrinkling or fraying. The narrow binder keeps the fabric from wrinkling or fraying. Often it has an edge that resembles fine fraying, though you as frequently, clearly, finished line will be found. Avoid the edge or your cut pieces as the pattern frequently differs from the main body of the fabric.

NOTE B: FABRIC WITH NAP OR DIRECTIONAL PATTERN
For fabric with a nap, such as velvet or corduroy, fabric with a directional pattern, such as plaid, you will need to cut the pattern pieces individually from the paper template, ensuring that the fold lines never cross on each pattern piece in the same direction.

NOTE C: USING FUSIBLE INTERFACING
Fusible interfacing is a material that is used to stiffen, strengthen, and stabilize certain pieces in a garment. When the type of fusible interfacing is specified, the pattern pieces should be marked with the following instructions: "Cut 2 Fusible" or "Cut 1 Fusible".

