

- SUPPLIES NEEDED**
- 2 1/2 YARDS OF 54" WIDE FABRIC
 - SHARP SCISSORS
 - REMOVABLE MARKING MEDIUM (chalk, wax, tailor's tack, etc.)
 - 1/2" NON-SEPARATING ZIPPER
 - THREAD
 - SEWING MACHINE
- Optional:**
- 1/2 YARD OF THINNER POCKET FABRIC
 - FUSIBLE INTERFACING

- CUTTING INSTRUCTIONS**
- Print pattern. You can print this document sheet on sheets of standard size paper and tape the pieces together, or print on a wide-format printer (36" or wider). These sheets offer the same size (or approximately 312" if available) as you, the PDF recommendations will format printing.
 - Once your pieces are printed, cut along the outermost rectangle to remove any excess paper. This template should fit exactly on a 54" wide or larger piece of fabric that has been folded in half. If your fabric is less than 54" wide see **NOTE A**. The maximum yield from this pattern is two cut for fabric that does not have a direction. For fabric with a nap, such as velvet or corduroy or fabric with a clear directional print see **NOTE B**.
 - Fold your fabric in half along the lengthwise grain marking (selvage edge or selvage edge). Schedule in the self-finished edge of fabric. The narrow border keeps the fabric from spreading or fraying. Once it has an edge that resembles any fraying, though not as frequently, a sharp finished line will be found. Avoid this edge in your cut pieces as the narrow frequently differs from the main body of the fabric.
 - Place the paper template on top your fabric, matching the folded edge of the fabric with the side of the paper marked "folded edge".
 - Place pins through-out the template pinning together both layers of fabric as well as the paper.
 - Cut around the perimeter of each piece.
 - Leaving the pins in place, you will need to stop each of the notches, taking care not to stop beyond the end of the 1/4" seam!

NOTE A: FABRIC LESS THAN 54" WIDE
If your fabric is less than 54" wide you will need to cut each pattern piece individually from the paper template and then arrange the pieces on your fabric using your own measurements. The quantity instructions and positions are all marked on each pattern piece to help you. To find the guidelines marking for 1/4" for the width line with two arrows at each end. There is also a marking for the direction of the fabric. To ensure that the pattern pieces fit, the distance from the top pattern piece to the edge of the fabric, this mark that the distance will be between arrows. When the top pattern piece is in place, the distance from the edge of the fabric that the pattern piece is correctly placed.

NOTE B: FABRIC WITH NAP OR DIRECTIONAL PATTERN
For fabric with a nap, such as velvet, corduroy, fabric with a clear directional print, or a matching pattern such as plaid, you will need to cut the pattern pieces individually. They are there to be cut with the grain, and the notches, seam lines on each pattern piece in the same direction.

NOTE C: USING FUSIBLE INTERFACING
Fusible interfacing is a material that can be used to stabilize, strengthen, and stabilize certain pieces in a garment. While the use of fusible interfacing is optional, the Railbird Denim Sewing Instructions Light to Medium weight instructions are more fully detailing the construction of J103017.

