JUMPSUIT
CUTTING INSTRUCTIONS

DOWNLOADED FROM JUMPSUIT-CUTTING-INSTRUCTIONS.IT © 2012
DIANA GARNETT

SUPPLIES NEEDED

- 1 YARD / METER OF WIDE FABRIC
- SHARP SCISSORS
- 1 YARD / METER OF MEDIUM SAUR, WOV, Nylon's tack, etc.)
- 1 - 20" NON-SEPARATING ZIPPER
- 1 BUTTON
- SEWING MACHINE
- THREAD
- 1 YD/M FABE OF THINNER POCKET FABRIC
- 1 FUSIBLE INTERFACING

CUTTING INSTRUCTIONS

1. Before cutting your fabric measure this square to make sure that the pattern is scaled correctly*. Some printers and software will automatically cut strips and shrink and edit pics file.
2. Some your pattern is printed, cut along the numerical rectangle to assess any cutter paper. This rectangle should measure 4" x 4" or 12cm x 12cm. If it does not measure exactly, you will need to adjust your printer settings. **NOTE A:** For maximum with the pattern is laid out for fabric that goes over a selvedge (for fabric with a nap, such as velvet or corduroy or fabric with a clear directional pattern) see **NOTE B.**
3. Cut out the pieces you need for your size. Pattern pieces are marked with the appropriate Size Demeter letters. Pattern pieces are cut out of fabric by placing a the of fabric edge of fabric. This section would cross the fabric from selvedge to Selvedge. Fold so the edge that is marked "Cut on Fold" is on the edge of the fabric. Place the pattern piece so that the edge of the pattern piece on the various Demeter(s) differs from the main body of the fabric.
4. Cut out the pattern pieces. Cut out the pieces you need for your size. Pattern pieces are marked with the appropriate Size Demeter letters. Place the edge of the pattern piece on the edge of the fabric.
5. Cut around the perimeter of each piece.
6. Cut out the pieces you need for your size. Pattern pieces are marked with the appropriate Size Demeter letters. Place the edge of the pattern piece on the edge of the fabric.
7. Cut around the perimeter of each piece.
8. Mark all pattern dots and notches.
9. Mark pattern dots and notches. Using a pen, bring together both layers of fabric and the pattern, mark the corner of each dot & notch with chalk, tacs or other removable, nonappearance tool. A tailor's tack may also be used.
10. Cut out the Fly Facing, Fly, Pocket Facing, Pocket Backing, Pocket Fabric, Pocket Fabric, Pocket Backing, Pocket Facing, Pocket Fabric, Pocket Backing, Pocket Facing, Pocket Fabric, Pocket Backing, Pocket Facing