

- SUPPLIES NEEDED**
- 3 1/3 YARDS OF 54" WIDE FABRIC
 - SEARS SCISSORS
 - REMOVABLE MARKING MEDIUM (chalk, wax, tailor's tack, etc.)
 - 1/2" NONSEPARATING ZIPPER
 - THREAD
 - SEWING MACHINE
- optional:
- 1/3 YARD OF THINNER POCKET FABRIC
 - FUSIBLE INTERFACING

CUTTING INSTRUCTIONS

1. Trace pattern. You can print this document (don't use sheets of standard size paper and tape the pieces together) or print on a wide-format printer (36" or wider). First, check for this service for approximately \$12. If available to you, the \$25 convenience kit is a great option.
2. Once your pattern is printed, cut along the outermost rectangle to remove any excess paper. This template should fit exactly on a 36" wide or larger piece of fabric that has been folded in half. If your fabric is less than 54" wide, use **NOTE A**. For maximum fold this pattern is laid out for fabric that does not have a direction. For fabric with a nap, such as velvet or tulle, or fabric with a clear directional grain, use **NOTE B**.
3. Fold your fabric on half along the lengthwise grain matching selvedge edge to selvedge edge. Selvedge is the self-finished edge of fabric. The narrow border along the fabric from selvedge to selvedge shows a hair on edge that resembles fine fringe, though not as frequently, a clearly finished line will be found. Avoid this edge in your cut pieces as the texture frequently differs from the main body of the fabric.
4. Place the paper template on top your fabric, matching the folded edge of the fabric with the side of the paper marked "folded edge".
5. Place pins throughout the template pinning together both layers of fabric as well as the paper.
6. Cut around the perimeter of each piece.
7. Leaving the pins in place, use your seam ripper to snip each of the notches, taking care to not snip beyond the end of the "fold".
8. **Notches are cut 1/4" deep markings that are placed throughout the pattern.** These notches indicate where allowances should be made, and where you will pin the pieces together when you sew.
9. Mark all notches with chalk, wax, or other removable, nonpermanent mark. A tailor's tack may also be used. These notches will be used to mark the pieces when you sew.
10. **Zipper** - Cut zipper pieces as directed on the pattern.
11. **OPTIONAL 1:** Cut fusible interfacing pieces (see **NOTE C** for more info). Pattern pieces that use fusible will be marked with the direction "Cut 2 Fusible" or "Cut 1 Fusible". These pieces are the Collar Fly, Fly Facing, Front Pocket Facing, and Front Pocket Backing. To cut the fusible, by the material down with the blue side facing up, then place your pattern down and cut around the perimeter of each piece and notch.
12. Cut the Front Pocket Bag out of a lighter pocketing material. If you are not using a pocketing material, then the Front Pocket Bag may be cut directly from the pattern piece. Pocketing is used in other tasks in case of disaster material - You will find an example of pocketing on any part of the jeans.

NOTE A: FABRIC LESS THAN 54" WIDE
If your fabric is less than 54" wide you will need to use each pattern piece on a separate piece of fabric. The pattern pieces are marked with arrows to indicate the grain direction. For fabric with a nap, such as velvet or tulle, or fabric with a clear directional grain, use **NOTE B**.

NOTE B: FABRIC WITH NAP OR DIRECTIONAL PATTERN
For fabric with a nap, such as velvet or tulle, or fabric with a clear directional grain, use **NOTE B**. The pattern pieces are marked with arrows to indicate the grain direction. For fabric with a nap, such as velvet or tulle, or fabric with a clear directional grain, use **NOTE B**.

NOTE C: USING FUSIBLE INTERFACING
Fusible interfacing is a material that is used to reinforce, stabilize and add structure to pattern pieces. When you use fusible interfacing, you will need to use the pattern pieces that are marked "Cut 2 Fusible" or "Cut 1 Fusible".

Before cutting your fabric measure this square to make sure that the pattern is scaled correctly*
**Some printers and software will automatically scale large scale images which will affect the fit.*

The inner square should measure 4" x 4"

The outer square should measure 12cm x 12cm

