JUMPSUIT
CUTTING INSTRUCTIONS

COPYRIGHT 2018 JUMPSUIT CUTTING INSTRUCTIONS V1.0
WWW.JUMPSUIT

SUPPLIES NEEDED

- 3 1/4 YARDS OF 54" WIDE FABRIC
- 1 YARD OF FUSIBLE
- IRON/CHALK MARKING MEDIUM (chalk, wax, tailor's tack, etc.)
- 1 - 24" NON-SEPARATING ZIPPER
- 1 - 1" BUTTON
- SEWING MACHINE

optional

- 1 YARD OF THINNER POCKET FABRIC
- FUSIBLE INTERFACING

CUTTING INSTRUCTIONS

1. Print pattern. You can print this document dial on sheets of standard size paper and tape the pieces together, or print on a large format printer. Staples Office Depot offer this service for approximately $12. If available in-store, the ADA recommends wide format printing.
2. Once your pattern is printed, cut along the outermost rectangle to remove any excess paper. This template should measure 8" x 10" and contain a smaller rectangle that measures 4" x 4". If your pattern does not, please see **NOTE A**. For maximum yield the pattern is laid out for fabric that does not have a direction. For fabric with a nap, such as velvet or corduroy or fabric with a clear directional print see **NOTE B**.
3. Cut out the pieces. Pieces are marked with a dashed line and should be cut on the line. Include the selvedge in the self finished edge of fabric. This ensures hooks-loops-bar tacks-fabric from unravelling or fraying. Often it has an edge that resembles nice fringe, though just as frequently, a clearly finished line will be found. Avoid this edge in your cut pieces. Cut the remainder of the selvedge off and toss it in the trash.
4. Place the paper templates on top your fabric, matching the folded edge of the fabric with the side of the paper marked "Fold on Edge".
5. Pin the paper templates to the fabric.
6. Cut around the perimeter of each piece.
7. Leaving the pins in place, you will need to snip each of the notches, taking care to not snip beyond the end of the notch.

Notches are 0.5" diagonal markings that are found throughout the pattern. Some notches indicate seam allowance widths, while others will help you match pieces together in the sewing.

8. Mark all notches drill holes. Using a pen, being together both layers of fabric and the pattern, mark the center of each drill hole with chalk, wax or other removable, nonpermanent tool. A tailor's tack may also be used.

Drill holes are found throughout the pattern and are marked with a ⊕.

They will be located on the Front Rack, Bodice Back, and Front pattern pieces but skirt the pattern pieces.

9. Cut the Front Pocket Backing, Front Pocket Facing, Fly Facing, Fly, Front Pocket Facing, and Front Pocket Backing. Cut on the bubble, lay the material down with the glue side facing up, place the pattern pieces on the material and cut around the perimeter of each piece.
10. Cut the Front Pocket Bag out of a lighter pocketing material. If you are not using a pocketing material, then the Front Pocket Bag may be cut alongside your other pattern pieces. Pocketing is used to reduce bulk in area of thicker material – *I use it for all pants except of pocketing or any part of the pant.*

NOTE A: FABRIC LESS THAN 54" WIDE

*Pattern is laid out for 54" wide fabric. If your fabric is narrower and pattern pieces will not fit, then the pieces should be cut in the following order: Cut the pieces that are longer than the pattern pieces to the three is natural wear. The pattern pieces that are longer than the pattern pieces are: and pattern pieces that are over 27 in. To find the position of the pieces, lay the pattern pieces on the fabric, and then, either and. Place lines indicate the direction, or pieces, of the pattern pieces. Place the pattern pieces on the fabric. Place the pattern pieces on the fabric. Place the pattern pieces on the fabric. To ensure that the cut parallel ensures the fabric. Place the pattern pieces on the fabric. Place the pattern pieces on the fabric. Place the pattern pieces on