

- SUPPLIES NEEDED**
- 3" **PIECES OF 54" WIDE FABRIC**
 - **SHARP SCISSORS**
 - **IRON/IRONING BOARD** (shulk, wax, holler's tack, etc.)
 - **1 - 26" NON-SEPARATING ZIPPER**
 - **THREAD**
 - **SEWING MACHINE**
- OPTIONAL:**
- **1/2 YARD OF THINNER POCKET FABRIC**
 - **FUSIBLE INTERFACING**

- CUTTING INSTRUCTIONS**
1. Print pattern on standard size paper and tape the pieces together, or print on a wide format printer (36" or wider). Print shops offer this service for approximately \$12. If available to you, the RDS recommends wide format printing.
 2. Once your pattern is printed, cut along the outermost rectangle to remove any excess paper. The template should be roughly one 1/4" wide or larger piece of fabric that has been folded in half. If your fabric is less than 1/4" wide, use **NOTE A**. For maximum fold the pattern is laid out for fabric that does not have a direction. For fabric with a grain, mark to indicate or indicate on fabric with a clear directional grain. **NOTE B**
 3. Fold your fabric in half along the lengthwise grain, matching a bridge edge to a bridge edge. Sew along the midline edge of fabric. This narrow border keeps the fabric from stretching or fraying. Once a line is sewn that resembles two layers, though not as frequently, a clearly finished line will be found. Avoid this edge in your cut pieces as the texture frequently differs from the main body of the fabric.
 4. Place the paper template on top your fabric, matching the folded edge of the fabric with the side of the paper marked "folded edge".
 5. Place pins throughout the template pinning together both layers of fabric as well as the paper.
 6. Cut around the perimeter of each piece.
 7. Leaving the pins in place, you will need to snip each of the notches, taking care to not snip beyond the end of the fabric.

NOTE A: FABRIC LESS THAN 1/4" WIDE
 If your fabric is less than 1/4" wide, you will need to use a wide format printer and a large piece of fabric. The paper template will need to be printed on a wide format printer. The paper template will need to be printed on a wide format printer. The paper template will need to be printed on a wide format printer.

NOTE B: FABRIC WITH NAIP OR DIRECTIONAL PATTERN
 If your fabric is a knit with a directional pattern, such as a stripe or plaid, you will need to use a wide format printer and a large piece of fabric. The paper template will need to be printed on a wide format printer. The paper template will need to be printed on a wide format printer.

NOTE C: USING FUSIBLE INTERFACING
 Fusible interfacing is a material that is used to stabilize, reinforce, and add structure to a garment. When the use of fusible interfacing is required, the fusible interfacing should be applied to the garment pieces individually first. Do this on one side of the fabric, ensuring that the interfacing is applied to the correct side of the fabric.

Size Feline Front Pocket Cut 2 Pocketing*

*or cut 2 self

Size Feline Back Waistband Cut 1 Self-On Fold

Size Feline Front Waistband Cut 2 Self

Size Feline Front Pocket Facing Cut 2 Self Cut 2 Fusible

Size Feline Sleeve Back Cut 2 Self

Size Feline Pant Back Cut 2 Self

Size Feline Collar Cut 2 Self Cut 2 Fusible

Size Feline Fly Cut 1 Self Cut 1 Fusible

Size Feline Fly Facing Cut 1 Self Cut 1 Fusible

Before cutting your fabric measure this square to make sure that the pattern is scaled correctly*
 *Some printers and software will automatically scale large scale images which will affect the fit.
 The inner square should measure 4" x 4"
 The outer square should measure 12cm x 12cm

Size Feline Sleeve Front Cut 2 Self

Size Feline Front Pocket Backing Cut 2 Self Cut 2 Fusible

Size Feline Pant Front Cut 2 Self

Belt Loops Cut 1 Self

Size Feline Bodice Back Cut 1 on Fold

Size Feline Bodice Front Cut 2 Self

Size Feline Back Pocket Cut 2 Self