JUMPSUIT
CUTTING INSTRUCTIONS

DESIGNED BY: MS. MARTHA LUPITA RODRIGUEZ-PEREZ, C.P.
DATE: 2020

SUPPLIES NEEDED
- 3/1 YARDS OF 54" WIDE FABRIC
- SHARP SCISSORS
- FABRIC MARKING MARKING MIDDLEIR (chalk, wax, tailor's tack, etc.)
- 1 - 24" NON-SEPARATING ZIPPER
- THREAD
- SEWING MACHINE
- PINS
- 1/2 YARD OF THINNER POCKET FABRIC
- FUSIBLE INTERFACING

CUTTING INSTRUCTIONS
1. Print pattern. You can print this document (that is) or choose of standard size paper and tape the pieces together, or print the pattern on large format paper. Make sure when printing, change either the scaling to 100% or uncheck the box that says "Fit to page" or "Scale to fit page" in the printer settings.
2. Once your pattern is printed, cut along the continuous rectangle to remove any excess paper. The rectangle should measure 4" x 4". Use this rectangle to ensure your pattern is printed to the correct scale. Place the rectangle on the square on the pattern and if the pattern is laid out in a fabric that does not have a directional pattern, you can cut the pattern in half along the fold line to save fabric. Place the pattern on the fabric with the grain line parallel to the selvage edge. Schedule in the pattern pieces and cut around the perimeter of each piece and notch.
3. Fold your fabric in half along the lengthwise grain matching selvage edge to selvage edge. Schedule in the pattern pieces and cut around the perimeter of each piece and notch. Pocketing is used in other built in use of fabric that resembles lace. Image, through use or frequently, a closely finished lace will be found. Avoid this edge on your pattern or the texture frequently differs from the main body of the fabric.
4. Cut out the pattern pieces. Transfer markings from the pattern to the fabric. Mark the folds with the side of the paper marked "FABRICS".
5. Cut out the pattern pieces. Transfer markings from the pattern to the fabric with the side of the paper marked "FABRICS".
6. Cut around the perimeter of each piece.
7. Notch the edges of pieces, you will need to rip each of the notches, taking care to rest snip beyond the end of the 1/4 inch.
   Notches are the 1/4 inch markings that are found throughout the pattern.
8. Mark the pattern pieces with the markings from the pattern. Mark the pattern pieces with ease.
   Ease is the difference between the measurements of the pattern and the pattern, mark the centers of each shell lock with chalk, wax or other removable, nonpermanent tool. Lock's lock may also be used.
   Ease is the difference between the measurements of the pattern and the pattern.
   This will be found on Pant Back, Pants Back, Back and front pattern.
   Ease is the difference between the measurements of the pattern and the pattern.
9. Sew the pieces together using a 5/8 inch seam allowance (1.5 cm seam ratio). Pressure pieces that are fusible will be marked with the direction "Cut 2 Fusible" or "Cut 2 Fusible". These pieces are the Collar, the Fly Facing, Front Pocket Facing, Front Pocket Backing, Pant Front, Pant Back, Bodice Back, Bodice Front, Back Pocket. Cut out these pieces, iron pressure down and cut around the perimeter of each piece and notch.
   Pocketing is used in other built in use of fabric that resembles lace. Image, through use or frequently, a closely finished lace will be found. Avoid this edge on your pattern or the texture frequently differs from the main body of the fabric.