JUMPSUIT
CUTTING INSTRUCTIONS

Sewing Pattern by Sarai
Illustration by Jessica Lee
Pattern Design by Jessica Lee and Sarai

SUPPLIES NEEDED
- **2-1 YARDS OF 44" WIDE FABRIC**
- **SMART SCISSORS**
- **1 ZIPPER, BRASS/SILVER, MEDIUM (chub, woo, tailor's tack, etc.)**
- **1 SET NON-SEPARATING ZIPPER**
- **1 SNAP**
- **SEWING MACHINE**
- **THREAD**
- **1/2 YARD OF FAMMER POCKET FABRIC**
- **1 SNAP PRESS**

CUTTING INSTRUCTIONS

1. Preparation: Iron pieces for clearance (feel free to choose of standard iron paper and tape, the pieces together, or print on a wide format printer (36" or wider). Photo shops offer this service for approximately $12. If available to you, this is a time saving option and recommended.
2. Once your pieces is printed, cut along the pattern rectangle to remove any excess paper. This template should measure 4" x 4". Place the template on the fabric, and cut around it. Repeat this process for all pieces. Note: **NOTE A** For clearance, fold the pattern it laid out for fabric that is wider than the pattern. Iron fabric with the pattern on it, and cut along the edge of the template. Repeat this process for all pieces.
3. Fold over fabric in half along the longitudinal grain matching selvedge edge to selvedge edge. Selvedge is the self finished edge of fabric. This matrix helps keep the fabric from stretching or flaring. Place it so that edge that is folded is on your left side, and the selvedge edge is on your right side. Place the pattern piece with the arrow on the screen (longwise) pillow down the main body of the fabric.
4. Place the pattern piece on the fabric so that the arrow is parallel to the fabric. Iron with the side of the paper marked "Folded edge."
5. Pin the pattern piece to the template pinning together both layers of fabric as well as the paper.
6. Cut around the perimeter of each piece.
7. Transfer the markings on the pattern piece onto the wrong side of the machine, taking care to mirror the mark of the 2 shapes.
8. Pin the pieces, original matching, for ease throughout the process.
9. Take matrix machine and enhance stable, solid white and high ease.
10. Pin pattern piece with using.
11. Sew the pieces together, with right sides, being angelica both layers of fabric and the pattern, mark the corner of each ball by with chalk, see, or other, marking tools, recommended tool. Leave each mark, pin the mark.
12. Sew the pieces together, with right sides, being angelica both layers of fabric and the pattern, mark the corner of each ball by with chalk, see, or other, marking tools, recommended tool. Leave each mark, pin the mark.
13. Pin the Front Pocket Backing to the Front Pocket Facing, right sides together. Sew along the curved edge. Pin Facing, Front Pocket Facing, and Front Pocket Backing. Do not sew the handle, for the seamed down with the glue side facing up. Iron the seam down, and sew the pocket facing and pocket backing together.
14. Fuse the Front Pocket Bag out of lighter pocketing material. If you are not using a pocketing material, then the Front Pocket Bag may be cut alongside your other pattern pieces. Pocketing is used to make half of your jr. dickie material. Use pull down or outside pocketing to cut out of this area.

NOTE A: FABRIC LESS THAN 54" WIDE
If your fabric is less than 54" wide you will need to use the pattern to make sure that the pattern is scaled correctly. Place the pattern piece on the fabric selvedge to selvedge. Place the pattern piece so that the arrow is parallel to the fabric selvedge. Place the pattern piece so that the inner square and outer square fit over all sides. Iron the pattern piece to the wrong side. Place the pattern piece on the fabric