

SUPPLIES NEEDED

- 3" (76.2cm) OF 1/4" WIDE FABRIC
- SHARP SCISSORS
- REMOVABLE MARKING MEDIUM (chalk, wax, tailor's tuck, etc.)
- 1 - 24" NON-SEPARATING ZIPPER
- IRON
- SEWING MACHINE
- SPREADER
- 1/2 YARD OF THINNER POCKET FABRIC
- FUSIBLE INTERFACING

CUTTING INSTRUCTIONS

1. Print pattern on standard size paper and tape the pieces together, or print on a wide format printer (36" or wider). Print sheets after this service for approximately \$12. If available to you, the BHS recommends wide format printing.

2. Once your pattern is printed, cut along the outermost rectangle to remove any excess paper. This template should fit exactly on 36" wide or larger pieces of fabric that has been folded in half. If your fabric is less than 36" wide use **NOTE A**.

3. Fold your fabric in half along the lengthwise grain matching selvage edge to selvage edge. Schedule in the self-finished edge of fabric. This narrow border from the fabric from centering or buying. Check if the selvage edge resembles: raw fringe, though just as frequently, a clearly finished line will be found. Avoid this edge in your cut pieces as the texture/weight differs from the main body of the fabric.

4. Place the paper template on top your fabric, matching the folded edge of the fabric with the side of the paper marked "folded edge".

5. Place pins throughout the template pinning together both layers of fabric as well as the paper.

6. Cut around the perimeter of each piece.

7. Leaving the pins in place, you will next need to strip each of the notches, taking care to not strip beyond the end of the shape.

8. **NOTE A:** If sharp markings and are found throughout the pattern, some areas may need alternate marking, while others will fit on the flat pattern piece itself.

9. Mark all corner fold lines. Using a pin, bring together both layers of fabric and the pattern, mark the corner of each fold with chalk, wax or other removable, non-permanent tool. A tailor's tuck may also be used.

10. **OPTIONAL:** Cut fusible interfacing pieces (see **NOTE C** for more info). Pattern pieces that use fusible will be marked with the direction "Cut 1 Fusible" or "Cut 2 Fusible". These pieces are the Collar, Fly, Fly Facing, Front Pocket Facing, and Front Pocket Backing. To cut the fusible, lay the material down with the glue side facing up, then place your pattern down and cut around the perimeter of each piece and notch.

11. Cut the Front Pocket Bag out of a lighter pecking material. If you are not using a pecking material, then the Front Pocket Bag may be cut alongside your other pattern pieces. **WARNING:** it will not adhere back to any glider or material - You will find an example of pecking on any part of this page.

NOTE A: FABRIC LESS THAN 36" WIDE

If your fabric is less than 36" wide, you will need to cut each pattern piece individually from the paper template and create corners or notches using pins to position the pattern pieces on the piece in a vertical state. The specific instructions and guidelines are detailed in additional notes below the pattern. The instructions are detailed in additional notes below the pattern. The instructions are detailed in additional notes below the pattern. The instructions are detailed in additional notes below the pattern.

NOTE B: FABRIC WITH NAP OR DIRECTIONAL PATTERN

If your fabric has a nap or directional pattern, you will need to cut each pattern piece individually from the paper template and create corners or notches using pins to position the pattern pieces on the piece in a vertical state. The specific instructions and guidelines are detailed in additional notes below the pattern. The instructions are detailed in additional notes below the pattern. The instructions are detailed in additional notes below the pattern.

NOTE C: USING FUSIBLE INTERFACING

Fusible interfacing is a material that is used to reinforce, stabilize and support pattern pieces that are made from a lightweight or non-stretch fabric. It is used to reinforce the collar, fly, fly facing, front pocket facing, and front pocket backing. It is used to reinforce the collar, fly, fly facing, front pocket facing, and front pocket backing. It is used to reinforce the collar, fly, fly facing, front pocket facing, and front pocket backing.

Size Xander Front Pocket Cut 2 Pocketing*

*or cut 2 self

Size Xander Back Waistband Cut 1 Self - On Fold

Size Xander Pant Back Cut 2 Self

Size Xander Collar Cut 2 Self Cut 2 Fusible

Size Xander Fly Cut 1 Self Cut 1 Fusible

Belt Loops Cut 1 Self

Size Xander Sleeve Front Cut 2 Self

Size Xander Pant Front Cut 2 Self

Size Xander Front Pocket Backing Cut 2 Self Cut 2 Fusible

Size Xander Bodice Back Cut 1 on Fold

Size Xander Fly Facing Cut 1 Self Cut 1 Fusible

Size Xander Front Waistband Cut 2 Self

Size Xander Bodice Front Cut 2 Self

Size Xander Front Pocket Facing Cut 2 Self Cut 2 Fusible

Size Xander Back Cut 2 Self

Before cutting your fabric measure this square to make sure that the pattern is scaled correctly*
 *Some printers and software will distort the fit.
 The inner square should measure 4" x 4"
 The outer square should measure 12cm x 12cm